

Material list

Dimension :5800*2250*2560mm		Remark
Frame	Main steel frame	8 PCS HANGING JOINT, 80C PURLINE 1.2mmMM thickness , 20*20square tube , upper & lower beam, 4 post, 40*80 square tube, inner hexagonal bolt (14*30) , 8 PCS L type connection parts, All the parts use galvanized steel material ,after welding electrostatic spray
	Color sheet capping	0.45mm Waterproof with butyl tape
	ceiling glass wool	50mm glass wool sandwich panel with single foil
	Ceiling tile	0.3mm 15 PCS
	Downpipes	φ50mm, L2670mm PVC 4 PCS
	Cement fiberboard	1157*2740*15mm
Interior decoration parts	Baseboard	PVC 5800*65mm 2 PCS, 2800*65mm 2 PCS
	Upper corner	PVC 5800*65mm 2 PCS, 2800*65mm 2 PCS
	Yin corner	PVC 2500mm 4PCS
Doo	Steel common door	0.4mm thickness, frane0.6mm,925*1970mm(only use for 50mm wall panel)
Windows	PVC windows	Single glass belt security window, screen window, 925*1100mm, 2 PCS

Sandwich panel	double side sheet 0.3mm	50mm thickness, Desnity 50kg/m3 Double-sided film
	50 U channel、 Hexagonal tail wire	
Electric matching	Standard electric matching	1 three-hole socket 2 five-hole socket 1 single open One LED ceiling light a six-circuit distribution box A 32A leakage protector One terminal (if need more ,please inform)
Only for order 2	6 sets of aisles	contain: 1 meter walkway board 1 3 meter walkway guardrail 1 0.98 meter guardrail 1 block 2 walkway brackets Canopy bracket 2 Full set of link bolts:16*40 bolts 4 4 nuts 4 spacers 5 bolts of 10*65 5 nuts 5 spacers 4 bolts of 10*120 4 nuts 4 spacers All use galvanized material after welding, the overall electrostatic spray
	6 canopies	contain: 3 m canopy board (with edging) Connecting bolt: 16*40 bolt 4 4 nuts 4 spacers 1 bolt of 10*65 1 nut 1 gasket
	Stair	contain: 1 staircase 1 stair handrail Stair support 2 Full set of link bolts: 14 bolts of 10*65 14 nuts 14 spacers All use galvanized material after welding, the overall electrostatic spray